



PRODUCT SUBMITTAL - SEISMIC PLASTIC CLIP



MATERIAL CONFORMANCE

Using a seismic plastic clip and continuous wire in brick veneer construction provides several important benefits related to structural integrity, safety, and resilience, particularly in seismic-prone areas.

This system adheres to the seismic regulations stipulated in the Uniform Building Code.

The Seismic Plastic Clip is firmly attached to the Clip ensuring secure fastening to the supporting structure.

Seismic Plastic Clip: (ASTM D4673-23)

Wire: (Carbon Steel) ASTM A1064 / A1064M

Tensile Strength: 80,000 psi. - Yield Point 70,000 psi.

Hot dip galvanized after fabrication

ASTM A153 / ASTM A153-B2 (1.5 oz/ft)

SIZES / FINISHES

The Seismic plastic clip includes ridges designed to hold standard 3Gen Triangles, Hooks, Barrel Anchor Wire Ties and Seismic Wire.

Seismic Plastic Clip:

Seismic Wire: 9 GA. 3/16"

RESET **EMAIL** **PRINT**

NOTE

The information contained on this submittal sheet does not constitute any professional opinion or judgement and should not be used as a substitute for any architect or engineer professional determinations. Each construction project is unique and the use of these products is the responsibility of the architects, engineers and other professionals who are familiar with the specific design of the project.

Mailing Address

8528 Davis Blvd., #134-246
North Richland Hills, TX 76182
Tel#: 1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive
Leeds, AL 35094
Tel#: 1-800-556-5785