



PRODUCT SUBMITTAL - BARREL ANCHOR WIRE TIE

The BWAT is used with the Barrel Anchors.



Material Conformance

85% Post-Consumer
10% Post-Industrial

Material Conformance

The BAWT is used with the Barrel anchors.
Recommended Spacing is 16" O.C., when using with the Barrel anchors
Meets TMS 402/602 & ACI / ASCE 530 Building Code Requirements and Specification for Masonary Structures
Wire: (Carbon Steel) ASTM A1064 / A1064M
Tensile Strength: 80,000 psi. - Yield Point 70,000 psi
Hot Dip Galvenized after fabrication
ASTM A153 / ASTM AL53-82 (1.5 oz/ft)

Product Details

BAWT Diameter: 3/16
BAWT Finish: Hot Dip Galvanized

BAWT Length

3" 4" 5" 6" 7"

RESET **EMAIL** **PRINT**

NOTE

The information contained on this submittal sheet does not constitute any professional opinion or judgement and should not be used as a substitute for any architect or engineer professional determinations. Each construction project is unique and the use of these products is the responsibility of the architects, engineers and other professionals who are familiar with the specific design of the project.

Mailing Address
8528 Davis Blvd., #134-246
North Richland Hills, TX 76182
Tel#: 1-800-556-5785

3genmp.com

Warehouse Address
8550 Parkway Drive
Leeds, AL 35094
Tel#: 1-800-556-5785