



PRODUCT SUBMITTAL - GENFLASH PRIMER



MATERIAL CONFORMANCE

GENFLASH Primer is a low viscosity, water-based formula designed to provide a tenacious bond in fully adhered, single ply roofing applications. GENFLASH Primer features a short dry time, making it an ideal product for applications dictated by production line speed. This material remains flexible once cured, allowing for expansion and contraction of the attached flashing membrane.

GENFLASH Primer must be applied to surfaces that are completely clean and free of any contaminants. It can be applied using a brush, squeegee, or spray equipment. Expected coverage is approximately 75 square feet per gallon, though this may vary based on the substrate's porosity.

SIZES / FINISHES

GENFLASH PRIMER

SIZE: 5 GALLON PAIL

****GENFLASH Primer is compatible with all 3GEN Flashing Products and Accessories****

RESET EMAIL PRINT

NOTE

The information contained on this submittal sheet does not constitute any professional opinion or judgement and should not be used as a substitute for any architect or engineer professional determinations. Each construction project is unique and the use of these products is the responsibility of the architects, engineers and other professionals who are familiar with the specific design of the project.

Mailing Address
8528 Davis Blvd., #134-246
North Richland Hills, TX 76182
Tel#: 1-800-556-5785

3genmp.com

Warehouse Address
8550 Parkway Drive
Leeds, AL 35094
Tel#: 1-800-556-5785