



PRODUCT SUBMITTAL - GENFLASH SEALANT



MATERIAL CONFORMANCE

GENFLASH Sealant is an Industrial and Construction Hybrid Sealant and Adhesive. A one-part, low odor, 100% solids, moisture-cure silyl-terminated polyether that will not shrink or crack and cures to a long-term durable rubber. It offers excellent resistance to UV degradation and yellowing for long-term performance in a broad range of indoor and outdoor applications. GENFLASH Sealant can be applied to wet substrates and in damp, humid environments which makes it immediately rain ready and mold and mildew resistant. It will even cure underwater. Eco-friendly & VOC compliant, it can be painted with most consumer and industrial latex paints.

SIZES / FINISHES

GENFLASH SEALANT

SIZE: ☐ 1 QUART TUBE

****GENFLASH Primer is compatible with all 3GEN Flashing Products and Accessories****

Sealant Coverage Chart 30 FL. OZ Tube								
Width								
Depth	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	287	144	96	72	58	48	41	36
1/4"		72	48	36	28.5	24	20.5	18
3/8"			11	8	6.5	5.5	4.5	4
1/2"				6	5	4	3.5	3

RESET EMAIL PRINT

NOTE

The information contained on this submittal sheet does not constitute any professional opinion or judgement and should not be used as a substitute for any architect or engineer professional determinations. Each construction project is unique and the use of these products is the responsibility of the architects, engineers and other professionals who are familiar with the specific design of the project.

Mailing Address
8528 Davis Blvd., #134-246
North Richland Hills, TX 76182
Tel#: 1-800-556-5785

3genmp.com

Warehouse Address
8550 Parkway Drive
Leeds, AL 35094
Tel#: 1-800-556-5785