

PRODUCT SUBMITTAL - CONTROL JOINT ANCHOR



Material Conformance:

Secures masonry walls and controls lateral displacement while permitting expansion and control joints to function intended. Field Bend on-site to join intersecting walls or tie new wall construction to existing structures.

Meets TMS 402/602 & ACI / ASCE 530 Building Code Requirements and Specification for Masonry Structures

Stainless Steel Wire Type 304
ASTM A580/ASTM 580M

Stainless Steel: Type 304 ASTM A240 / A240M,
ASTM A480 / A480M & ASTM A666.

Sizes/Finishes:

Control Joint Anchor:

Type 304 Stainless Steel

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

The information provided herein is for general informational purposes only and does not constitute a professional opinion or engineering judgment. It is not intended to replace the design, detailing, or project-specific determinations of the licensed architect or engineer of record. Each project is unique. The selection, application, suitability, and proper installation of these products are the sole responsibility of the design professional and installer based on project-specific conditions, substrate, exposure, and applicable codes. All products and information referenced herein are subject to 3GEN Masonry Products, Inc.'s Terms and Conditions of Sale, including all limitations of liability, disclaimers of warranties, and exclusive remedies, as published and in effect at the time of sale..

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785