


PRODUCT SUBMITTAL - DOUBLE EYE

Double Eyes are used with Hook (Pintle)



Recycled Content:

Mill Galvanized & Hot Dip Galvanized
85% Post-Consumer
10% Post-Industrial

Stainless Steel Type 304/316
68% Post- Consumer
18% Pre-Consumer

Material Conformance:

Double Eyes are used with Hook (Pintle) Recommended

Spacing is 16" O.C.

Meets TMS 402/602 & ACI / ASCE 530 Building Code
Requirements and Specification for Masonry Structures

Wire: (Carbon Steel) ASTM A1064 / A1064M

Tensile Strength: 80,000 psi. - Yield Point 70,000 psi. Hot Dip
Galvanized after fabrication.

ASTM A153 / ASTM A153-B2 (1.5 oz/ft²)

Stainless Steel ASTM 580 / ASTM 580M – Type 304 or 316

Product Details:

Double Eye Diameter: 3/16"

Double Eye Finish: Hot Dip Galvanized Stainless Steel 304
316 Stainless Steel is available on special order

Double Eye Length:

4 3/4" 5 3/4"

In order to email your submittal sheet information, you must have Adobe Acrobat
installed on your computer.

NOTE

The information provided herein is for general informational purposes only and does not constitute a professional opinion or engineering judgment. It is not intended to replace the design, detailing, or project-specific determinations of the licensed architect or engineer of record.

Each project is unique. The selection, application, suitability, and proper installation of these products are the sole responsibility of the design professional and installer based on project-specific conditions, substrate, exposure, and applicable codes.

All products and information referenced herein are subject to 3GEN Masonry Products, Inc.'s Terms and Conditions of Sale, including all limitations of liability, disclaimers of warranties, and exclusive remedies, as published and in effect at the time of sale.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785