

PRODUCT SUBMITTAL - GENFLASH® PRIMER



Material conformance:

GENFLASH® Primer is a low viscosity, water-based formula designed to provide a tenacious bond in fully adhered, single ply roofing applications. GENFLASH® Primer features a short dry time, making it an ideal product for applications dictated by production line speed. This material remains flexible once cured, allowing for expansion and contraction of the attached flashing membrane.

GENFLASH® Primer must be applied to surfaces that are completely clean and free of any contaminants. It can be applied using a brush, squeegee, or spray equipment. Expected coverage is approximately 75 square feet per gallon, though this strate's porosity.

Sizes/Finishes:

GENFLASH® PRIMER

SIZE:

5 GALLON PAIL

GENFLASH® Primer is compatible with all 3GEN Flashing Products and Accessories

NOTE

The information contained on this submittal sheet does not constitute any professional opinion or judgement and should not be used as a substitute for any architect or engineer professional determinations. Each construction project is unique and the use of these products is the responsibility of the architects, engineers and other professionals who are familiar with the specific design of the project.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785