

PRODUCT SUBMITTAL - GENFLASH® PRIMER



Material conformance:

GENFLASH® Primer is a low viscosity, water-based formula designed to provide a tenacious bond in fully adhered, single ply roofing applications. GENFLASH® Primer features a short dry time, making it an ideal product for applications dictated by production line speed. This material remains flexible once cured, allowing for expansion and contraction of the attached flashing membrane.

GENFLASH® Primer must be applied to surfaces that are completely clean and free of any contaminants. It can be applied using a brush, squeegee, or spray equipment. Expected coverage is approximately 75 square feet per gallon, though this varies with the substrate's porosity.

Sizes/Finishes:

GENFLASH® PRIMER

SIZE:

5 GALLON PAIL

****GENFLASH® Primer is compatible with all 3GEN Flashing Products and Accessories****

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

All information, data, and recommendations on this submittal are provided for general informational purposes only and do not constitute any warranty, guarantee, representation, or professional opinion. No reliance shall be placed on this information. Product selection, suitability, design, installation, and code compliance are the sole responsibility of the architect, engineer, design professional, and contractor. All Products are provided subject to 3GEN Masonry Products, Inc. Terms and Conditions of Sale, including all limitations, disclaimers, exclusive remedies, and indemnity obligations.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785