PRODUCT SUBMITTAL - GENFLASH® PRIMER

Material conformance:

GENFLASH® Primer is a low viscosity, water-based formula designed to provide a tenacious bond in fully adhered, single ply roofing applications. GENFLASH® Primer features a short dry time, making it an ideal product for applications dictatedby production line speed. This material remains flexible once cured, allowing for expansion and contraction of the attached flashing membrane.

GENFLASH® Primer must be applied to surfaces that are completely clean and free of any contaminants. It can be applied using a brush, squeegee, or spray equipment. Expected coverage is approximately 75 square feet per gallon, though this strate's porosity.

Sizes/Finishes:

GENFLASH® PRIMER

SIZE:

☐ 5 GALLON PAIL

****GENFLASH® Primer is compatible with all 3GEN Flashing Products and Accessories****

Reset | Print | Email

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

The information provided herein is for general informational purposes only and does not constitute a professional opinion or engineering judgment. It is not intended to replace the design, detailing, or project-specific determinations of the licensed architect or engineer of record.
Each project is unique. The selection, application, suitability, and proper installation of these products are the sole responsibility of the design professional and installer based on project-specific conditions, substrate, exposure, and applicable codes.
All products and information referenced herein are subject to 3GEN Masonry Products, Inc.'s Terms and Conditions of Sale, including all limitations of liability, disclaimers of warranties, and exclusive remedies, as published and in effect at the time of sale.

Mailing Address
8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address
8620 Spruiell Street NE,
Leeds, AL 35094 Tel#:
1-800-556-5785