PRODUCT SUBMITTAL - H-10 Seismic Triangle

The H-10 Seismic Triangle veneer anchor is used for anchoring brick to metal stud, wood stud, concrete block or poured concrete.



Recycled Content:

Hot Dip Galvanized	Stainless Steel Type 304/316
85% Post-Consumer	68% Post-Consumer
10% Post-Industrial	18% Pre-Consumer

Material conformance:

The H-10 veneer anchor is used for anchoring brick to metal stud, wood stud, concrete block or poured concrete

Recommended Spacing is 16" O.C. and should not be installed on top of insulation.

Meets TMS 402/602 & ACI / ASCE 530 Building Code Requirements and Specification for Masonry Structures

Sheet Metal: ASTM A1008 / A1008M

Wire: (Carbon Steel) ASTM A1064 / A1064M

Tensile Strength: 80,000 psi. - Yield Point 70,000 psi.

Hot dip galvanized after fabrication

ASTM A153 / ASTM A153-B2 (1.5 oz/ft^2)

Stainless Steel: ASTM 580 / ASTM 580M – Type 304 or 316

Structural Performance:

The 14 ga H-10 anchor can withstand 100+ lbs. in both tension and compression without deforming or developing play more than 0.05" The 12 ga H-10 anchor exceeds 400 lbs. under the same test conditions. Test results available upon request.

Sizes/Finishes:

H-10 Finish: ☐ Hot Dip Galvanized ☐ 304 SS

H-10 Material Thickness

☐ 14 Gauge ☐ 12 Gauge

Triangle Diameter: 3/16"

Triangle Finish: ☐ Hot Dip Galvanized ☐ 304 SS

Triangle Length: ☐ 3" ☐ 4" ☐ 5" ☐ 6" ☐ 7" ☐ 9"

Reset | Print | Email

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

The information provided herein is for general informational purposes only and does not constitute a professional opinion or engineering judgment. It is not intended to replace the design, detailing, or project-specific determinations of the licensed architect or engineer of record. Each project is unique. The selection, application, suitability, and proper installation of these products are the sole responsibility of the design professional and installer based on project-specific conditions, substrate, exposure, and applicable codes.
All products and information referenced herein are subject to 3GEN Masonry Products, Inc.'s Terms and Conditions of Sale, including all limitations of liability, disclaimers of warranties, and exclusive remedies, as published and in effect at the time of sale.

Mailing Address
8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address
8620 Spruiell Street NE,
Leeds, AL 35094 Tel#:
1-800-556-5785