



PRODUCT SUBMITTAL - H-13-H

The H-13-H veneer anchor is used for anchoring brick to metal stud, wood stud, concrete block or poured concrete.



Anchor can be installed Horizontal or Vertical.



Recycled Content:

Mill Galvanized & Hot Dip Galvanized
85% Post-Consumer 10% Post-Industrial

Material Conformance:

The H-13-H veneer anchor is used for anchoring brick to metal stud, wood stud, concrete block or poured concrete.

H-13-H can be used with rigid or spray foam insulation.

This anchor's multifunctional design allows for horizontal installation with a hook or vertical installation with a triangle.

Recommended Spacing is 16" O.C.

Meets TMS 402/602 & ACI / ASCE 530 Building Code Requirements and Specification for Masonry Structures

Sheet Metal: ASTM A1008 / A1008M

Wire: (Carbon Steel) ASTM A1064 / A1064M

Tensile Strength: 80,000 psi. - Yield Point 70,000 psi.

Hot dip galvanized after fabrication.

ASTM A153 / ASTM A153-B2 (1.5 oz/ft)

Structural Performance:

Capable of withstanding 100 lbs load in tension and compression without deforming or developing play in excess of .05 inch. (Test results available upon request)

Product Details:

H-13 Finish:	Hot Dip Galvanized	304 Stainless Steel			
H-13 Material Thickness:	14 Gauge				
Hook Diameter:	3/16"	Hook Finish: Hot Dip Galvanized			
Thickness:		304 Stainless Steel			
	0"	1"	1 1/2"	2"	2 1/2"
	3"	3 1/2"	4"	4 1/2"	
3/16" Diameter Hook (Pintle) Length:					
	3"	4"	5"	6"	7"

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

All information, data, and recommendations on this submittal are provided for general informational purposes only and do not constitute any warranty, guarantee, representation, or professional opinion. No reliance shall be placed on this information. Product selection, suitability, design, installation, and code compliance are the sole responsibility of the architect, engineer, design professional, and contractor. All Products are provided subject to 3GEN Masonry Products, Inc. Terms and Conditions of Sale, including all limitations, disclaimers, exclusive remedies, and indemnity obligations.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785