


PRODUCT SUBMITTAL - REBAR POSITIONER

Rebar Positioners are used to properly locate the rebar in the cores of the CMU.



Recycled Content:

85% Post-Consumer 10% Post-Industrial

Material Conformance:

Rebar Positioners are used to properly locate the rebar in cores of the CMU.

Wire: (Carbon Steel) ASTM A1064 / A1064M

Tensile Strength: 80,000 psi. - Yield Point 70,000 psi.

Hot Dip Galvanized after fabrication.

ASTM A153 / ASTM A153-B2 (1.5 oz/ft²)

Product Details:

Rebar Positioner Diameter: 9 gauge (.148")

Rebar Positioner Finish: Hot Dip Galvanized

Rebar Positioner: ☐ Single ☐ Twin Rebar ☐ Twin Wide

Positioner CMU Size:

☐ 6" ☐ 8" ☐ 10" ☐ 12"

Reset

Print

Email

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

The information provided herein is for general informational purposes only and does not constitute a professional opinion or engineering judgment. It is not intended to replace the design, detailing, or project-specific determinations of the licensed architect or engineer of record.

Each project is unique. The selection, application, suitability, and proper installation of these products are the sole responsibility of the design professional and installer based on project-specific conditions, substrate, exposure, and applicable codes.

All products and information referenced herein are subject to 3GEN Masonry Products, Inc.'s Terms and Conditions of Sale, including all limitations of liability, disclaimers of warranties, and exclusive remedies, as published and in effect at the time of sale.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8620 Spruiell Street NE,
Leeds, AL 35094 Tel#:
1-800-556-5785