


PRODUCT SUBMITTAL - TEK SCREWS



Recycled Content::

85% Post-Consumer
10% Post-Industrial

Material Conformance:

The Tek Screws are used to secure veneer ties such as the H-10 & H-13 to the metal stud backup.

Recommended Spacing of anchor is 16" O.C

Wire: (Carbon Steel) ASTM A1064 / A1064M
Tensile Strength: 80,000 psi. - Yield Point 70,000 psi.

Conforms to:
ASTM C954
ASTM B117

Product Details:

Tek Screw Diameter: #10 with EPDM Washer

Tek Screw Length:

1 1/2"

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

All information, data, and recommendations on this submittal are provided for general informational purposes only and do not constitute any warranty, guarantee, representation, or professional opinion. No reliance shall be placed on this information. Product selection, suitability, design, installation, and code compliance are the sole responsibility of the architect, engineer, design professional, and contractor. All Products are provided subject to 3GEN Masonry Products, Inc. Terms and Conditions of Sale, including all limitations, disclaimers, exclusive remedies, and indemnity obligations.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785