

PRODUCT SUBMITTAL - TERMINATION BAR - TYPE F (FLAT)



Recycled Content:

Stainless Steel (Type 304) 68%

Post-Consumer

18% Post-Industrial

Aluminum

60% Post-Consumer

20% Post-Industrial

Material conformance:

Termination Bar (Flat) is used to mechanically secure the top of surface mounted flashing to the substrate and is compatible with all flashing products.

Recommended fastening of Termination Bar (Flat) is 8" o.c.

Stainless Steel: Type 304 ASTM A240 / A240M,

ASTM A480 / A480M & ASTM A666.

Aluminum ASTM B221 / ASTM B221M

Sizes/Finishes:

Termination Bar (Flat) Size: 1/8" x 1" x 8ft long.

Holes: 9/32" diameter holes spaced 8" o.c.

Termination Bar (Flat) Finish:

Aluminum

Stainless Steel (Type 304)

In order to email your submittal sheet information, you must have Adobe Acrobat installed on your computer.

NOTE

The information contained on this submittal sheet does not constitute any professional opinion or judgement and should not be used as a substitute for any architect or engineer professional determinations. Each construction project is unique and the use of these products is the responsibility of the architects, engineers and other professionals who are familiar with the specific design of the project.

Mailing Address

8528 Davis Blvd., #134-246 North
Richland Hills, TX 76182 Tel#:
1-800-556-5785

3genmp.com

Warehouse Address

8550 Parkway Drive Leeds,
AL 35094 Tel#:
1-800-556-5785